

Wide Range Analog Input Module (WAIM)

Fully Qualified Safety-Related Digital Platform

**CURTISS-
WRIGHT**



About

Curtiss-Wright Nuclear has partnered with Radics, LLC to supply integrated FPGA-based instrumentation and control (I&C) systems for nuclear power plants and research reactors. RadICS is a digital I&C platform that is robust, flexible, and scalable. It provides state-of-the-art functions, services, and safeguards for safety applications in the nuclear industry. The RadICS product line consists of a Logic Module, basic input/output modules, and specialty modules all housed in a seismically qualified chassis.

The Wide Range Analog Input Module serves as a high density analog field sensor acquisition module. It provides 32 independent, highly reliable, and galvanically isolated inputs with built-in filtering, calibration, and analog to digital conversion for use by the Logic Module. The Wide Range Analog Input Module also performs robust and continuous self-diagnostics to ensure the safety and integrity of each input and module function.

Wide Range Analog Input Module (WAIM)

- High density 32 channel analog inputs with built-in hardware redundancy and self-diagnostics for highly reliable operation, filtering, calibration, and random hardware failure detection.
- Independent FPGA for data communication, self-diagnostics, and fail-safe functional behavior.
- Robust self-diagnostics give early fault detection for safety-focused fault management.
- Segregation of communications processing, self-diagnostics, and watchdog functions assures safety critical functionality.
- Galvanic isolation for external communication lines with robust and dedicated communication links to Logic Module for secure data transfer.
- Inherent on-board diversity features eliminate common cause failure vulnerabilities.
- FPGA technology ensures resilience to I&C obsolescence.



Wide Range Analog Input Module (WAIM)

Fully Qualified Safety-Related Digital Platform

Wide Range Analog Input Module Technical Specifications

Function	Specifications
Input Analog Signal Range	$\pm 10\text{ V}$ ($\pm 11.5\text{ V}$ over-range monitoring capability) Differential input impedance: not less than 1 megohm
A/D Conversion Resolution	18 bits / 400 kilo samples per second (kSPS)
Response Time	5 milliseconds
Common Mode Rejection Ratio	> 86 dB
Overall Accuracy	0.04% of full scale (@ 25 °C)
Input Channel Isolation	All input channels are galvanic-isolated up to 250 V _{RMS} AC or 250 VDC field-to-chassis and channel-to-channel
Overvoltage Protection	$\pm 60\text{ VAC/VDC}$ continuous (using external protection elements installed in chassis)
Information Package Exchange Cycle	5 milliseconds
Diagnostic Package Exchange Cycle	5 milliseconds
LVDS Line Speed	100 megabit/second
LVDS Line Protocol	Proprietary protocol with integrity checking (CRC), galvanic-isolated Tx / Rx
Self-Diagnostic Functions	Diverse watchdog unit, checksum analysis, active diagnostics with internal fault detection, hardware error detection, functionally diverse continuous self-diagnostic tests, power supply fault detection
Power Supply / Consumption	2 independent inputs – 24 (18 – 36) VDC / Maximum consumption: 1.01A ($\pm 0.15\text{ A}$) (32 inputs used; -10V input value at each input)
Indications	2 status LED indicators (RUN/FAULT) 4-character dot matrix symbol-indicator for providing current operational mode, service information, and error codes
Operating Temperature	4.4 to 60 °C (40 to 140 °F)
Operating Humidity	10 to 90% relative humidity, non-condensing

CONTACT INFORMATION:

1350 Whitewater Dr., Idaho Falls, ID 83402 USA
Tel: +1.208.497.3535 | DSS-Sales@curtisswright.com